

TECHNICAL CHARACTERISTICS

URANIA FE

PRODUCT CODE: 1347

APPLICATION

Synthetic multigrade motor oil for turbocharged and aspirated diesel engines of commercial vehicles. It permits reduction of fuel consumption, long drain intervals up to the highest mileages recommended by OEM's on the new generation engines.

SPECIFICATIONS

SAE 5W-30, ACEA E4/E7, API CF, IVECO 18-1804 FE, MB 228.5, VOLVO VDS-3, SCANIA LDF, MAN M3277, MACK EO-M Plus, RENAULT RVI RXD PERFORMANCE, DAF HP1/HP2, MTU OIL TYPE 3, CUMMINS CES 20071/20072/20076/20077

TEST DESCRIPTION

| TEST DESCRIPTION | METHOD | UNIT | TYPICAL VALUE |
|-------------------------|-------------|----------|---------------|
| APPEARANCE | -- | -- | B. & C. |
| SPECIFIC GRAVITY @ 15°C | ASTM D 1298 | -- | 0,860 |
| VISCOSITY @ 100°C | ASTM D 445 | cSt | 11,4 |
| VISCOSITY INDEX | ASTM D 2270 | -- | 165 |
| FLASH POINT CI. O. C. | ASTM D 92 | °C | 220 |
| T.B.N. | ASTM D 2896 | mg KOH/g | 16 |
| POUR POINT | ASTM D 97 | °C | -36 |
| FOAM @ 24°C | ASTM D 892 | cc/s | 0 |

All technical data is provided for reference only.