

TECHNICAL CHARACTERISTICS

URANIA MAXIMO 5W-30

PRODUCT CODE: 2166

APPLICATION

Synthetic multigrade motor oil for turbocharged and aspirated Diesel engines of commercial vehicles. It permits reduction of fuel consumption, long drain intervals up to the highest mileages recommended by OEM's on the new generation engines.

SPECIFICATIONS

SAE 5W-30, ACEA E4/E7, API CF, MB-Approval 228.5, MAN M3277, VOLVO VDS-3, SCANIA LDF, RENAULT RVI RXD Performance, MACK EO-M Plus, DAF HP1/HP2, MTU OIL TYPE 3

TEST DESCRIPTION

TEST DESCRIPTION	METHOD	UNIT	TYPICAL VALUE
APPEARANCE	--	--	B. & C.
DENSITY 15°C	ASTM D 4052	g/cm ³	0,865
VISCOSITY @ 100°C	ASTM D 445	cSt	11,5
VISCOSITY INDEX	ASTM D 2270	--	165
T.B.N.	ASTM D 2896	mg KOH/g	15
FLASH POINT CI. O. C.	ASTM D 92	°C	220
POUR POINT	ASTM D 97	°C	<-33
FOAM @ 24°C	ASTM D 892	cc/s	0

All technical data is provided for reference only.