

TECHNICAL CHARACTERISTICS

URANIA TURBO LD
PRODUCT CODE: 1333

APPLICATION

Mineral engine oil for trucks and industrial vehicles with all types of turbo engines as well as light commercial vehicles with aspirated engines. The product ensures maximum protection against wear and greatly facilitates start-up. Extended drain interval.

SPECIFICATIONS

SAE 15W-40, ACEA E3, API CF, IVECO 18-1804, MB 228.3, VOLVO VDS-2, MAN QC 13-017/M3275, RENAULT RVI RD Performance, ALLISON C4

TEST DESCRIPTION

TEST DESCRIPTION	METHOD	UNIT	TYPICAL VALUE
APPEARANCE	--	--	B. & C.
SPECIFIC GRAVITY @ 15°C	ASTM D 1298	--	0,891
VISCOSITY @ 100°C	ASTM D 445	cSt	14,8
VISCOSITY INDEX	ASTM D 2270	--	140
FLASH POINT Cl. O. C.	ASTM D 92	°C	214
T.B.N.	ASTM D 2896	mg KOH/g	14,5
POUR POINT	ASTM D 97	°C	-30
FOAM @ 24°C	ASTM D 892	cc/s	TRACES/0

All technical data is provided for reference only.

RESEARCH & DEVELOPMENT

04/2008